

2 MP 10X OUTDOOR IP CAMERA

2 Mega-Pixels | H.264 | PoE | IP66 | 10X Optical | Easy Installation | Micro SD Card | Night Version



IPC-230P2



Key Features

Support easy installation with NAT transversal DDNS server for port setting free

Compact size and stylish design with full function of I/O interface

Support advanced setting of WDR, 3D NR, Auto Iris, Low Lux mode, Exposure control

Support Smart focus / Auto focus / Step focus

Support H.264 / MPEG4 / MJPEG multi-codec and multi-streaming

Support connectivity with iPhone, smart phones and all browsers including Firefox, Chrome, Safari and Opera

Support 2 way audio

Built-in Samba function to store image/video at local area network directly

Built-in Micro-SD Card slot for easy storing and playback image/video

Built-in Motion Detection & Email Notification

10 times optical zoom , 4 times digital zoom

Up to 30 fps at 1920 x 1080 of video resolution

High power IR LEDs with mechanical ICR and auto light sensor for day and night monitoring

Complied with IP66 for outdoor installation

Free bundled 64CH recording software

Package

Camera, Power Adapter, Bracket, Installation Software & Manual on CD, Quick Installation Guide

Viewing System Requirement

Operation System: Microsoft Windows XP / VISTA / 7 / 8 | iOS | Android

Browser: Internet Explorer 6.X or Above, FireFox, Chrome, Safari and Opera

Technical Specifications

2 Mega Pixels 10X Optical Zoom Outdoor IP Camera

System	RAM: 4GB DDR ROM: 16MB Flash ROM
Camera Specification	1/2.7 inch color CMOS sensor Resolution: 1920 x 1080 1.0 Lux / F2.0, AGC, AWB, AEC
Lens	10X Optical Zoom Lens, Auto Iris, Auto Focus f = 4.9~ 49mm, F1.8~3.0 FoV (D): 7.2° ~ 66.6°
Video Resolution	Up to 30 Frames per Second at 1920 x 1080, 1280 x 1024, 1280 x 800, 640 x 480, 320 x 240 and 176 x 144
Audio	G.711/AMR/AAC, Omni-directional Microphone Support 2 way audio
Infrared LED	Auto / Manual Mode , 25~ 30 M visible High Power IR LEDs
Protocol	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP and RTSP
Algorithm supported	H.264 / MPEG4 / MJPEG Multi-Codec for streaming video JPEG for still image
Physical	10 base T or 100 base T Fast Ethernet Auto Negotiation
I/O Interface	RJ-45, DI, Audio In, Audio Out, Video Out, Micro SD (Inside Camera)
Power	Input: 100-240VAC, 50/60Hz, 0.7A Output: 12VDC, 1.5A Consumption: Max 10 W Support 802.3af Compliant Power over Ethernet (PoE)
Operating Environment	Temperature : -20 - 50°C Humidity : 85% RH
Dimension	75 Dia. x 165 (mm)
Weight	NET. 600 g, WithBracket 800 g
EMI & Safety	CE & FCC

Products specifications and design subject to change without notice