

# 2M IP CAMERA

2 Mega-Pixels | H.264 | Easy Installation | SD Card | Night Version



IPC-620V2

IPC-620G2



## Key Features

Support easy installation with NAT transversal DDNS server for port setting free

Support H.264 / MPEG4 / MJPEG multi-codec and multi-streaming

Support connectivity with various kind of browser including Firefox, Chrome, Safari and Opera

Support connectivity with iPhone, smart phone and Tablet-PC

Support RTSP - Real Time Streaming Protocol

Support Wi-Fi Protected Setup - WPS Key for easy wireless setup (Wireless model only)

Built-in Samba function to store image/video at local area network directly

Built-in microphone for audio monitoring

Built-in SD Card slot for easy storing and playback image / video

Built-in USB hard disc slot

Built-in Motion Detection & Email Notification

Up to 30 fps at 1920 x 1080 of video resolution

12 IR LEDs with ICR and auto light sensor for day and night monitoring

Adjustable manual focus, auto white balance, auto exposure control

Free bundled 64CH recording software

## Package

Camera, Power Adapter, Camera stand, Installation Software & Manual on CD, Quick Installation Guide, Antenna (wireless model)

## Viewing System Requirement

Operation System: Microsoft Windows XP / VISTA / 7 / 8

Browser: Internet Explorer 6.X or Above, FireFox, Chrome, Safari and Opera

## Technical Specifications

### 2 Mega Pixels IP Camera

<b>System</b>	RAM: 4GB DDR ROM: 16MB Flash ROM
<b>Camera Specification</b>	1/2.7 inch color CMOS sensor Resolution: 1920 x 1080 1.0 Lux / F2.0 AGC, AWB, AEC
<b>Lens</b>	Fixed 4.0mm Focal Length / F2.0 with fine tuning View Angle: 62 degree
<b>Video Resolution</b>	Up to 30 Frames per Second at 1920 x 1080, 1280 x 1024, 1280 x 800, 640 x 480, 320 x 240 and 176 x 144
<b>Audio</b>	AMR / G.276 Omni-Directional Microphone
<b>Infrared LED</b>	Auto / Manual Mode Daylight Sensor, Angle +/- 65 Wave Length 400~ 700nm Spectral Band width 42nm Peak Emission Wave Length 850nm
<b>Protocol</b>	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP and RTSP
<b>WLAN (Wireless Model Only)</b>	802.11b/g/n Wireless LAN Security: WEP/WPA-PSK/WPA2-PSK
<b>Algorithm supported</b>	H.264 / MPEG4 / MJPEG Multi-Codec for streaming video JPEG for still image
<b>Physical</b>	10 base T or 100 base T Fast Ethernet Auto Negotiation
<b>Power</b>	Input: 100-240VAC, 50/60Hz, 0.7A Output: 12VDC, 1.5A Consumption: Max 12 W
<b>Operating Environment</b>	Temperature : 0 - 40°C Humidity : 85% RH
<b>Dimension</b>	108 x 67 x 28 (mm)
<b>Weight</b>	NET. 120g (Wired Model) NET. 135g (Wireless Model)
<b>EMI &amp; Safety</b>	CE & FCC

Products specifications and design subject to change without notice